


真 中 平 角 管

(定 尺 売 り)

JIS 規格名及記号 H3300 C2700T
 旧JIS 規格名及記号 H3631 BSBM2 快削真中棒 2種普通級
 配 合 (%) Cu63.0~67.0
 Pb0.07以下 Fe0.05以下 Zn残部
 質 別 H
 比 重 8.53

(単位m/m)

辺 の 外 ・ 内 径 公 差	4以上	15以下	±0.08
	15を超え	25 "	±0.09
	25 "	50 "	±0.12
	50 "	75 "	±0.15
	75 "	100 "	±0.20
	100 "	125 "	±0.27

肉 厚 mm	た て mm	横 mm	長 さ mm	1 本 重 量 kg	備 考
0.45	3	5	2,500	0.141	★寸法呼称 
1.0	5	10	2,500	0.500	
1.0	5	15	2,500	0.792	
0.8	6	10	2,500	0.507	
1.0	6	10	2,500	0.620	
0.8	6	12	2,500	0.576	
1.0	6	12	2,500	1.706	
1.0	6	15	2,500	0.835	
1.0	7	20	3,000	1.312	
1.0	7	30	6,000	1.828	
1.0	8	12	2,500	0.792	
1.0	8	15	2,500	0.921	
1.0	8	20	4,000	1.818	
1.2	9	24	4,000	2.569	
1.0	10	15	4,000	1.612	
1.5	10	15	4,000	2.337	
1.2	10	20	4,000	2.321	
1.2	10	25	4,000	2.734	
1.2	10	30	4,000	3.146	
1.0	12	20	4,000	2.093	
1.2	12	20	4,000	2.486	
1.0	12	24	4,000	2.368	
1.5	12	24	4,000	3.472	
1.2	12	25	4,000	2.899	
1.0	15	24	4,000	2.575	

一口メモ 丹銅とは、銅が84~86%、鉛が0.05%以下、鉄が0.05H、亜鉛残部の配合で色沢が美しく、展延性、絞り性、耐食性が良い。建築用、装身具、化粧品ケースに用いられます。

真中平角管

(定尺売り)

肉厚 mm	たて mm	横 mm	長さ mm	1本重量 kg	備考
1.5	15	24	4,000	3.781	
1.0	15	30	4,000	2.988	
1.5	15	30	4,000	4.400	
1.5	15	40	4,000	5.432	
1.5	15	50	4,000	6.464	
1.0	18	30	4,000	3.194	
1.5	18	30	4,000	4.710	
1.5	20	30	4,000	4.916	
1.5	20	40	4,000	5.948	
1.5	20	50	4,000	6.980	
1.5	25	40	4,000	6.464	
1.5	25	45	4,000	6.980	
1.5	25	50	4,000	7.496	
1.6	30	60	4,000	9.629	
2.0	30	60	4,000	11.950	
1.8	38	76.2	5,000	17.238	
2.0	40	80	5,000	20.097	
2.0	50	100	5,000	25.256	