

# ステンレス丸棒 SUS 3 1 6

(一部切断売り)

JIS 規格名及記号 G4303 SUS316

配 合 (%) C 0.08以下 Si1.00 以下 Mn2.00以下  
P0.040以下 S0.03以下 Ni10.00~14.00  
Cr 16.00~18.00 Mo2.00~3.00

仕 上 げ 酸洗及びピーリング  
比 重 7.98

(単位：m/m)

| 径     | 外径公差   | 長さ公差 |
|-------|--------|------|
| 28φ以下 | ±0.4   | 乱尺   |
| 30φ～  | ±1.5 % | "    |

| 径<br>mm | 長 さ<br>mm | 1 m 当り 参 考<br>重 量 kg | 表 面<br>仕 上 | 切 断<br>可 否 | 無 計 量<br>採 用 | 備 考 |
|---------|-----------|----------------------|------------|------------|--------------|-----|
| 6       | 4.4m乱尺    | 0.226                | 酸 洗        | —          | ×            |     |
| 8       | "         | 0.401                | "          | —          | ×            |     |
| 9       | "         | 0.51                 | "          | —          | ×            |     |
| 10      | "         | 0.63                 | "          | —          | ×            |     |
| 12      | "         | 0.90                 | "          | —          | ×            |     |
| 13      | "         | 1.06                 | "          | —          | ×            |     |
| 14      | "         | 1.23                 | "          | —          | ×            |     |
| 16      | "         | 1.60                 | "          | —          | ×            |     |
| 18      | "         | 2.03                 | "          | —          | ×            |     |
| 19      | "         | 2.26                 | "          | —          | ×            |     |
| 20      | "         | 2.51                 | ピーリング      | 可          | ×            |     |
| 22      | "         | 3.03                 | "          | "          | ×            |     |
| 24      | "         | 3.61                 | "          | "          | ×            |     |
| 25      | 5.5m乱尺    | 3.92                 | "          | "          | ×            |     |
| 26      | "         | 4.24                 | "          | "          | ×            |     |
| 28      | "         | 4.91                 | "          | "          | ×            |     |
| 30      | "         | 5.64                 | "          | "          | ×            |     |
| 32      | "         | 6.42                 | "          | "          | ×            |     |
| 34      | "         | 7.24                 | "          | "          | ×            |     |
| 35      | "         | 7.68                 | "          | "          | ×            |     |
| 36      | "         | 8.12                 | "          | "          | ×            |     |
| 38      | "         | 9.05                 | "          | "          | ×            |     |
| 40      | "         | 10.03                | "          | "          | ×            |     |
| 42      | "         | 11.1                 | "          | "          | ×            |     |
| 44      | "         | 12.13                | "          | "          | ×            |     |
| 45      | "         | 12.7                 | "          | "          | ×            |     |
| 46      | "         | 13.3                 | "          | "          | ×            |     |

×印は計量する寸法です。

一口メモ SUS316 は SUS304 に対して更に耐食性を改善した鋼種です。

# ステンレス丸棒 S U S 3 1 6

(一部切断売り)

| 径<br>mm | 長さ<br>mm | 1 m 当り 参考<br>重 量 kg | 表 面<br>仕 上 | 切 断<br>可 否 | 無 計 量<br>採 用 | 備 考 |
|---------|----------|---------------------|------------|------------|--------------|-----|
| 48      | 5.5m乱尺   | 14.43               | ピーリング      | 可          | ×            |     |
| 50      | "        | 15.7                | "          | "          | ×            |     |
| 55      | "        | 19.0                | "          | "          | ×            |     |
| 60      | "        | 22.6                | "          | "          | ×            |     |
| 65      | "        | 26.5                | "          | "          | ×            |     |
| 70      | "        | 30.7                | "          | "          | ×            |     |
| 75      | "        | 35.3                | "          | "          | ×            |     |
| 80      | "        | 40.1                | "          | "          | ×            |     |
| 85      | "        | 45.26               | "          | "          | ×            |     |
| 90      | "        | 50.74               | "          | "          | ×            |     |
| 95      | "        | 56.54               | "          | "          | ×            |     |
| 100     | "        | 62.64               | "          | "          | ×            |     |
| 110     | "        | 75.80               | "          | "          | ×            |     |
| 120     | "        | 90.21               | "          | "          | ×            |     |
| 130     | "        | 105.87              | "          | "          | ×            |     |
| 140     | "        | 122.78              | "          | "          | ×            |     |
| 150     | "        | 140.95              | "          | "          | ×            |     |
| 160     | 4m~5m 乱尺 | 160.37              | ターニング      | "          | ×            |     |
| 170     | "        | 181.04              | "          | "          | ×            |     |
| 180     | "        | 202.96              | "          | "          | ×            |     |
| 190     | "        | 226.14              | "          | "          | ×            |     |
| 200     | "        | 250.57              | "          | "          | ×            |     |
| 210     | "        | 276.26              | "          | "          | ×            |     |
| 220     | "        | 303.19              | "          | "          | ×            |     |
| 230     | "        | 331.38              | "          | "          | ×            |     |
| 240     | "        | 360.82              | "          | "          | ×            |     |
| 250     | "        | 391.52              | "          | "          | ×            |     |
| 260     | "        | 423.47              | "          | "          | ×            |     |

×印は計量する寸法です。

一口メモ 材質識別の為両端面に赤色のスプレーをしています。

# ステンレス丸棒 SUS 4 3 0 (センターレス)

JIS 規格名及記号 G4318 SUS430  
比 重 7.7

| 径<br>mm | 長 さ<br>mm | 1 m当り参考<br>重 量 kg | 表 面<br>仕 上 | 切 断<br>可 否 | 備 考 |
|---------|-----------|-------------------|------------|------------|-----|
| 4       | 2,000     | 0.097             | センターレス     | 否          |     |
| 5       | "         | 0.151             | "          | "          |     |
| 6       | "         | 0.218             | "          | "          |     |
| 7       | "         | 0.296             | "          | "          |     |
| 8       | "         | 0.387             | "          | "          |     |
| 9       | "         | 0.490             | "          | "          |     |
| 10      | "         | 0.604             | "          | "          |     |
| 11      | "         | 0.731             | "          | "          |     |
| 12      | "         | 0.870             | "          | "          |     |
| 13      | "         | 1.022             | "          | "          |     |
| 14      | "         | 1.185             | "          | "          |     |
| 15      | "         | 1.360             | "          | "          |     |
| 16      | "         | 1.547             | "          | "          |     |
| 17      | "         | 1.747             | "          | "          |     |
| 18      | "         | 1.958             | "          | "          |     |
| 19      | "         | 2.182             | "          | "          |     |
| 20      | "         | 2.418             | "          | "          |     |
| 25      | "         | 3.778             | "          | "          |     |
| 30      | "         | 5.440             | "          | "          |     |

# ステンレス丸棒 S U S 4 3 0 （ピーリング）

比 重 7.75

| 径<br>mm | 長 さ<br>mm     | 1 m当り参考<br>重 量 kg | 表 面<br>仕 上 | 切 断<br>可 否 | 備 考 |
|---------|---------------|-------------------|------------|------------|-----|
| 22      | 4,000～6,000乱尺 | 2.944             | ピーリング      | 可          |     |
| 24      | 〃             | 3.504             | 〃          | 〃          |     |
| 25      | 〃             | 3.802             | 〃          | 〃          |     |
| 28      | 〃             | 4.770             | 〃          | 〃          |     |
| 30      | 〃             | 5.475             | 〃          | 〃          |     |
| 32      | 〃             | 6.230             | 〃          | 〃          |     |
| 35      | 〃             | 7.453             | 〃          | 〃          |     |
| 36      | 〃             | 7.885             | 〃          | 〃          |     |
| 38      | 〃             | 8.785             | 〃          | 〃          |     |
| 40      | 〃             | 9.734             | 〃          | 〃          |     |
| 42      | 〃             | 10.732            | 〃          | 〃          |     |
| 45      | 〃             | 12.320            | 〃          | 〃          |     |
| 48      | 〃             | 14.017            | 〃          | 〃          |     |
| 50      | 〃             | 15.209            | 〃          | 〃          |     |

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS304 |        | SUS304L |        | SUS316 |        | SUS316L |        |
|---------|--------|--------|---------|--------|--------|--------|---------|--------|
|         | 在庫寸法   | 表面状態   | 在庫寸法    | 表面状態   | 在庫寸法   | 表面状態   | 在庫寸法    | 表面状態   |
| 8       | ○      | SD, KC |         |        | ○      | SD, KC | ○       | SD, KS |
| 9       | ○      | "      |         |        | ○      | "      |         |        |
| 10      | ○      | "      | ○       | SD, KC | ○      | "      | ○       | SD, KC |
| 12      | ○      | "      |         |        | ○      | "      | ○       | SD, KS |
| 13      | ○      | SD     | ○       | SD     | ○      | SD     | ○       | SD     |
| 14      | ○      | "      | ○       | SD     | ○      | "      | ○       | "      |
| 16      | ○      | "      | ○       | SD     | ○      |        | ○       | SD     |
| 18      | ○      | PM     |         |        | ○      | PM     |         |        |
| 19      | ○      | "      | ○       | SD     | ○      | "      | ○       | SD     |
| 20      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 22      | ○      | "      | ○       | PM     | ○      | "      | ○       | PM     |
| 24      | ○      | "      |         |        | ○      | "      |         |        |
| 25      | ○      | "      | ○       | PM     | ○      | "      | ○       | PM     |
| 26      | ○      | "      |         |        | ○      | "      |         |        |
| 28      | ○      | "      | ○       | PM     | ○      | "      | ○       | PM     |
| 30      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 32      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 34      | ○      | "      |         |        | ○      | "      |         |        |
| 35      | ○      | "      | ○       | PM     | ○      | "      | ○       | PM     |
| 36      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 38      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 40      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 42      | ○      | "      | ○       | "      | ○      | "      | ○       | "      |
| 44      | ○      | "      |         |        | ○      | "      |         |        |
| 45      | ○      | "      | ○       | PM     | ○      | "      | ○       | PM     |
| 46      | ○      | "      |         |        | ○      | "      | ○       | "      |
| 48      | ○      | "      |         | PM     | ○      | "      | ○       | "      |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
TR ラフターニング、KR矯正ロール

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS304 |      | SUS304L |      | SUS316 |      | SUS316L |      |
|---------|--------|------|---------|------|--------|------|---------|------|
|         | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態 |
| 50      | ○      | PM   | ○       | PM   | ○      | PM   | ○       | PM   |
| 55      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 60      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 65      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 70      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 75      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 80      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 85      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 90      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 95      | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 100     | ○      | "    | ○       | "    | ○      | "    | ○       | "    |
| 105     | ○      | "    |         |      |        |      |         |      |
| 110     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 115     | ○      | "    |         |      |        |      |         |      |
| 120     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 125     | ○      | "    |         |      |        |      |         |      |
| 130     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 135     | ○      | "    |         |      |        |      |         |      |
| 140     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 145     | ○      | "    |         |      |        |      |         |      |
| 150     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 155     | ○      | "    |         |      |        |      |         |      |
| 160     | ○      | "    | ○       | PM   | ○      | PM   | ○       | PM   |
| 170     | ○      | TM   |         |      | ○      | TM   | ○       | TM   |
| 180     | ○      | "    |         |      | ○      | "    | ○       | "    |
| 190     | ○      | "    |         |      | ○      | "    | ○       | "    |
| 200     | ○      | "    |         |      | ○      | "    | ○       | "    |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径             | SUS304 |      | SUS304L |      | SUS316 |      | SUS316L |      |
|---------------------|--------|------|---------|------|--------|------|---------|------|
|                     | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態 |
| 210                 | ○      | TM   |         |      | ○      | TM   |         |      |
| 220                 | ○      | "    |         |      | ○      | "    | ○       | TM   |
| 230                 | ○      | "    |         |      | ○      | "    | ○       | TM   |
| 240                 | ○      | "    |         |      | ○      | "    | ○       | TM   |
| 250                 | ○      | "    |         |      | ○      | "    |         |      |
| 260                 | ○      | "    |         |      | ○      | "    |         |      |
| 270                 | ○      | "    |         |      |        |      |         |      |
| 280                 | ○      | "    |         |      |        |      |         |      |
| 290                 | ○      | "    |         |      |        |      |         |      |
| 300                 | ○      | "    |         |      |        |      |         |      |
| 310                 | ○      | "    |         |      |        |      |         |      |
| 320                 | ○      | "    |         |      |        |      |         |      |
| 330                 | ○      | "    |         |      |        |      |         |      |
| 340                 | ○      | "    |         |      |        |      |         |      |
| 350                 | ○      | "    |         |      |        |      |         |      |
| 360                 | ○      | "    |         |      |        |      |         |      |
| 380                 | ○      | "    |         |      |        |      |         |      |
| 400                 | ○      | "    |         |      |        |      |         |      |
| 切断販売しております。         |        |      |         |      |        |      |         |      |
| 当該在庫品以外についてもご一報下さい。 |        |      |         |      |        |      |         |      |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

# JIS G 4303 ステンレス丸鋼

< 切断売り・一部在庫 >

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS303 |      | SUS310S |        | SUS321 |      | SUS329J I |      |
|---------|--------|------|---------|--------|--------|------|-----------|------|
|         | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態   | 在庫寸法   | 表面状態 | 在庫寸法      | 表面状態 |
| 8       |        |      | ○       | SD, KC |        |      |           |      |
| 10      | ○      | SD   | ○       | "      |        |      |           |      |
| 13      | ○      | "    | ○       | SD     | ○      | SD   | ○         | SD   |
| 14      | ○      | "    |         |        |        |      |           |      |
| 16      | ○      | "    | ○       | SD     | ○      | SD   | ○         | SD   |
| 18      | ○      | PM   |         |        |        |      |           |      |
| 19      | ○      | "    | ○       | SD     | ○      | SD   | ○         | SD   |
| 20      | ○      | "    | ○       | "      |        | PM   |           |      |
| 22      | ○      | "    | ○       | PM     | ○      | "    | ○         | SD   |
| 24      | ○      | "    |         |        |        |      |           |      |
| 25      | ○      | "    | ○       | "      |        | "    |           |      |
| 26      | ○      | "    |         |        | ○      | PM   | ○         | SD   |
| 28      | ○      | "    | ○       | PM     | ○      |      | ○         | "    |
| 30      | ○      | "    | ○       | "      | ○      | PM   |           |      |
| 32      | ○      | "    | ○       | "      | ○      | "    | ○         | SD   |
| 34      | ○      | "    |         |        | ○      | "    |           |      |
| 35      | ○      | "    | ○       | PM     | ○      | PM   |           |      |
| 36      | ○      | "    | ○       | "      |        |      | ○         | SD   |
| 38      | ○      | "    | ○       | "      | ○      | PM   | ○         | "    |
| 40      | ○      | "    | ○       | "      | ○      | "    | ○         | PM   |
| 42      | ○      | "    | ○       | "      | ○      | "    | ○         | "    |
| 45      | ○      | "    | ○       | "      | ○      | "    |           |      |
| 46      | ○      | "    | ○       | "      |        |      | ○         | PM   |
| 48      | ○      | "    |         |        |        |      |           |      |
| 50      | ○      | "    | ○       | PM     | ○      | PM   | ○         | PM   |
| 55      | ○      | "    | ○       | "      | ○      | "    | ○         | "    |
| 60      | ○      | "    | ○       | "      | ○      | "    | ○         | "    |
| 65      | ○      | "    | ○       | "      | ○      | "    | ○         | "    |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール



# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS303 |      | SUS310S |      | SUS321 |      | SUS329J I |      |
|---------|--------|------|---------|------|--------|------|-----------|------|
|         | 在庫寸法   | 表面状態 | 在庫寸法    | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法      | 表面状態 |
| 70      | ○      | PM   | ○       | PM   | ○      | PM   | ○         | PM   |
| 75      | ○      | "    | ○       | "    | ○      | "    | ○         | "    |
| 80      | ○      | "    | ○       | "    | ○      | "    | ○         | "    |
| 85      | ○      | "    | ○       | "    |        |      |           |      |
| 90      | ○      | "    | ○       | "    | ○      | PM   | ○         | PM   |
| 95      | ○      | "    | ○       | "    |        |      |           |      |
| 100     | ○      | "    | ○       | "    | ○      | PM   | ○         | PM   |
| 110     | ○      | "    | ○       | "    | ○      | "    | ○         | "    |
| 120     | ○      | "    | ○       | "    | ○      | "    | ○         | "    |
| 130     | ○      | "    | ○       | "    | ○      | "    | ○         | PM   |
| 140     | ○      | "    | ○       | "    | ○      | "    |           |      |
| 150     | ○      | "    | ○       | "    | ○      | PM   | ○         | PM   |
| 160     | ○      | "    |         |      |        |      |           |      |
| 170     | ○      | TM   |         |      |        |      |           |      |
| 180     | ○      | "    |         |      |        |      |           |      |
| 190     | ○      | "    |         |      |        |      |           |      |
| 200     | ○      | "    |         |      |        |      |           |      |
| 210     | ○      | "    |         |      |        |      |           |      |
| 220     | ○      | "    |         |      |        |      |           |      |
| 230     | ○      | "    |         |      |        |      |           |      |
| 240     | ○      | "    |         |      |        |      |           |      |
| 250     | ○      | "    |         |      |        |      |           |      |
| 260     | ○      | "    |         |      |        |      |           |      |
| 270     | ○      | "    |         |      |        |      |           |      |
| 280     | ○      | "    |         |      |        |      |           |      |
| 290     | ○      | "    |         |      |        |      |           |      |
| 300     | ○      | "    |         |      |        |      |           |      |

切断販売しております。  
当該在庫品以外についてもご一報下さい。

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

# JIS G 4303 ステンレス丸鋼

(16φ以上切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS403 |      | SUS420J2 |      | SUS304N2 |        | SUS304BF |      |
|---------|--------|------|----------|------|----------|--------|----------|------|
|         | 在庫寸法   | 表面状態 | 在庫寸法     | 表面状態 | 在庫寸法     | 表面状態   | 在庫寸法     | 表面状態 |
| 8       | ○      | KC   | ○        | KC   |          |        |          |      |
| 9       | ○      | "    | ○        | "    | ○        | KC. SD |          |      |
| 10      | ○      | "    | ○        | "    |          |        |          |      |
| 12      | ○      | "    | ○        | "    |          |        |          |      |
| 13      | ○      | KR   | ○        | KR   | ○        | KC. SD |          |      |
| 14      | ○      | "    | ○        | "    |          |        |          |      |
| 15      |        |      |          |      |          |        |          |      |
| 16      | ○      | KR   | ○        | KR   | ○        | SD     |          |      |
| 18      | ○      | "    | ○        | "    |          |        |          |      |
| 19      | ○      | "    | ○        | "    | ○        | PM     |          |      |
| 20      | ○      | PM   | ○        | PM   | ○        | "      |          |      |
| 22      | ○      | "    | ○        | "    | ○        | "      |          |      |
| 23      |        |      |          |      |          |        |          |      |
| 24      | ○      | PM   | ○        | PM   |          |        |          |      |
| 25      | ○      | "    | ○        | "    | ○        | PM     | ○        | PM   |
| 26      | ○      | "    | ○        | "    |          |        |          |      |
| 28      | ○      | "    | ○        | "    | ○        | PM     |          |      |
| 30      | ○      | "    | ○        | "    | ○        | "      |          |      |
| 32      | ○      | "    | ○        | "    | ○        | "      | ○        | PM   |
| 34      | ○      | "    | ○        | "    |          |        |          |      |
| 35      |        |      |          |      | ○        | PM     |          |      |
| 36      | ○      | PM   | ○        | PM   |          |        |          |      |
| 38      | ○      | "    | ○        | "    | ○        | PM     | ○        | PM   |
| 40      | ○      | "    | ○        | "    | ○        | "      |          |      |
| 42      | ○      | "    | ○        | "    |          |        |          |      |
| 44      | ○      | "    | ○        | "    |          |        |          |      |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径 | SUS403 |      | SUS420J2 |      | SUS304N2 |      | SUS304BF |      |
|---------|--------|------|----------|------|----------|------|----------|------|
|         | 在庫寸法   | 表面状態 | 在庫寸法     | 表面状態 | 在庫寸法     | 表面状態 | 在庫寸法     | 表面状態 |
| 45      | ○      | PM   | ○        | PM   | ○        | PM   | ○        | PM   |
| 46      | ○      | "    | ○        | PM   |          |      | ○        | PM   |
| 48      | ○      | "    | ○        | "    |          |      | ○        | "    |
| 50      | ○      | "    | ○        | "    | ○        | PM   | ○        | "    |
| 55      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 60      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 65      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 70      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 75      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 80      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 85      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 90      | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 95      | ○      | "    | ○        | "    |          |      |          |      |
| 100     | ○      | "    | ○        | "    | ○        | PM   | ○        | PM   |
| 110     | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 120     | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 130     | ○      | "    | ○        | "    |          |      | ○        | "    |
| 140     | ○      | "    | ○        | "    | ○        | "    | ○        | "    |
| 150     | ○      | "    | ○        | "    |          |      | ○        | "    |
| 160     | ○      | "    | ○        | "    |          |      |          |      |
| 170     | ○      | TM   | ○        | TM   |          |      | ○        | TM   |
| 180     | ○      | "    | ○        | "    |          |      | ○        | "    |
| 190     | ○      | "    | ○        | "    |          |      | ○        | "    |
| 200     | ○      | "    | ○        | "    |          |      | ○        | "    |
| 210     | ○      | "    | ○        | "    |          |      |          |      |
| 220     | ○      | "    | ○        | "    |          |      |          |      |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

(切断売り・一部在庫)

○印取扱品

切断販売しております。  
当該在庫品以外についてもご一報下さい。

— 236 —

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

16φ以上切断可

○印取扱品

| 鋼種<br>径 | SUS440C |      | SUS630 |      | YUS170 |      | SUS416 |      |
|---------|---------|------|--------|------|--------|------|--------|------|
|         | 在庫寸法    | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法   | 表面状態 |
| 3       | 2000    |      |        |      |        |      |        |      |
| 4       | "       | D    |        |      |        |      |        |      |
| 5       | "       | "    |        |      |        |      |        |      |
| 6       | "       | "    |        |      |        |      |        |      |
| 7       | "       | "    |        |      |        |      |        |      |
| 8       | ○       | KC   |        |      |        |      |        |      |
| 10      | ○       | "    | ○      | KC   |        |      |        |      |
| 13      | ○       | A    | ○      | A    | ○      | PM   |        |      |
| 16      | ○       | "    | ○      | "    | ○      | "    | ○      | PM   |
| 18      |         |      | ○      |      |        |      | ○      | "    |
| 19      | ○       | "    | ○      | "    |        |      |        |      |
| 20      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 22      | ○       | "    | ○      | "    | ○      | PM   | ○      | "    |
| 24      |         |      |        |      |        |      | ○      | "    |
| 25      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 26      | ○       | "    | ○      | "    | ○      | PM   | ○      | "    |
| 28      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 30      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 32      | ○       | "    | ○      | "    | ○      | PM   | ○      | "    |
| 34      |         |      | ○      | "    |        |      | ○      | "    |
| 36      | ○       | A    | ○      | A    |        |      | ○      | "    |
| 38      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 40      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 42      | ○       | "    | ○      | "    | ○      | PM   | ○      | "    |
| 45      | ○       | "    | ○      | "    |        |      |        |      |
| 46      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 48      |         |      |        |      |        |      | ○      | "    |
| 50      | ○       | "    | ○      | "    | ○      | PM   | ○      | "    |
| 55      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 60      | ○       | "    | ○      | "    |        |      | ○      | "    |
| 65      | ○       | "    | ○      | "    |        |      | ○      | "    |

記号内容 S D 酸洗 K C 矯正カット P M ピーリング T M ターニング A 黒皮  
D 引き抜き T R ラフターニング K R 矯正ロール

# JIS G 4303 ステンレス丸鋼

(切断売り・一部在庫)

Stainless Steel Bars

○印取扱品

| 鋼種<br>径             | SUS440C |      | SUS630 |      | YUS170 |      |      |      |
|---------------------|---------|------|--------|------|--------|------|------|------|
|                     | 在庫寸法    | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法   | 表面状態 | 在庫寸法 | 表面状態 |
| 70                  | ○       | A    | ○      | A    |        |      | ○    | PM   |
| 75                  | ○       | "    | ○      | "    |        |      | ○    | "    |
| 80                  | ○       | TR   | ○      | TR   | ○      | PM   | ○    | "    |
| 85                  | ○       | "    | ○      | "    |        |      | ○    | "    |
| 90                  | ○       | "    | ○      | "    | ○      | PM   | ○    | "    |
| 95                  | ○       | "    | ○      | "    |        |      | ○    | "    |
| 100                 | ○       | "    | ○      | "    |        |      | ○    | "    |
| 110                 | ○       | "    | ○      | "    |        |      | ○    | "    |
| 120                 | ○       | "    | ○      | "    | ○      | TM   | ○    | "    |
| 130                 | ○       | "    | ○      | "    |        |      | ○    | "    |
| 140                 | ○       | "    | ○      | "    |        |      | ○    | "    |
| 150                 | ○       | "    | ○      | "    | ○      | TM   | ○    | "    |
| 160                 | ○       | TM   | ○      | TM   |        |      |      |      |
| 180                 | ○       | "    | ○      | "    |        |      |      |      |
| 190                 | ○       | "    | ○      | "    |        |      |      |      |
| 200                 | ○       | TM   | ○      | "    |        |      |      |      |
| 切断販売しております。         |         |      |        |      |        |      |      |      |
| 当該在庫品以外についてもご一報下さい。 |         |      |        |      |        |      |      |      |

記号内容 SD 酸洗 KC 矯正カット PM ピーリング TM ターニング A 黒皮  
D 引き抜き TR ラフターニング KR 矯正ロール

# ステンレス丸鋼重量表

| 鋼種別記号 | 比 重  | 適 用 鋼 種                                                                      |
|-------|------|------------------------------------------------------------------------------|
| A     | 7.93 | S U S 304, 304 L, 321, 329 J <sub>1</sub> , 303, 304 B F, 304 N <sub>2</sub> |
| B     | 7.98 | S U S 316, 316 L, 309 S, 310 S                                               |
| C     | 7.75 | S U S 403, 420 J <sub>2</sub>                                                |

| 径<br>mm | 断 面 積<br>cm <sup>2</sup> | 重量 A<br>kg / m | 重量 B<br>kg / m | 重量 C<br>kg / m | 径<br>mm | 断 面 積<br>cm <sup>2</sup> | 重量 A<br>kg / m | 重量 B<br>kg / m | 重量 C<br>kg / m |
|---------|--------------------------|----------------|----------------|----------------|---------|--------------------------|----------------|----------------|----------------|
| 6       | 0.2827                   | 0.224          | 0.226          | 0.219          | 45      | 15.90                    | 12.6           | 12.7           | 12.3           |
| 7       | 0.3848                   | 0.305          | 0.307          | 0.298          | 46      | 16.62                    | 13.2           | 13.3           | 12.9           |
| 8       | 0.5027                   | 0.399          | 0.401          | 0.390          | 48      | 18.10                    | 14.3           | 14.4           | 14.0           |
| 9       | 0.6362                   | 0.504          | 0.508          | 0.493          | 50      | 19.64                    | 15.6           | 15.7           | 15.2           |
| 10      | 0.7854                   | 0.623          | 0.627          | 0.609          | 55      | 23.76                    | 18.9           | 19.0           | 18.4           |
| 11      | 0.9503                   | 0.754          | 0.758          | 0.737          | 60      | 28.27                    | 22.4           | 22.6           | 21.9           |
| 12      | 1.131                    | 0.897          | 0.903          | 0.877          | 65      | 33.18                    | 26.3           | 26.5           | 25.7           |
| 13      | 1.327                    | 1.05           | 1.06           | 1.03           | 70      | 38.48                    | 30.5           | 30.7           | 29.8           |
| 14      | 1.539                    | 1.22           | 1.23           | 1.19           | 75      | 44.18                    | 35.0           | 35.3           | 34.2           |
| 15      | 1.767                    | 1.40           | 1.41           | 1.37           | 80      | 50.27                    | 39.9           | 40.1           | 39.0           |
| 16      | 2.011                    | 1.59           | 1.60           | 1.56           | 85      | 56.75                    | 45.0           | 45.3           | 44.0           |
| 17      | 2.270                    | 1.81           | 1.81           | 1.76           | 90      | 63.62                    | 50.4           | 50.8           | 49.3           |
| 18      | 2.545                    | 2.02           | 2.03           | 1.97           | 95      | 70.88                    | 56.2           | 56.6           | 54.9           |
| 19      | 2.835                    | 2.25           | 2.26           | 2.20           | 100     | 78.54                    | 62.3           | 62.7           | 60.9           |
| 20      | 3.142                    | 2.49           | 2.51           | 2.43           | 105     | 86.59                    | 68.7           | 69.1           | 67.1           |
| 21      | 3.464                    | 2.75           | 2.76           | 2.68           | 110     | 95.03                    | 75.4           | 75.8           | 73.7           |
| 22      | 3.801                    | 3.01           | 3.03           | 2.95           | 115     | 103.9                    | 82.4           | 82.9           | 80.5           |
| 23      | 4.155                    | 3.29           | 3.32           | 3.22           | 120     | 113.1                    | 89.7           | 90.3           | 87.7           |
| 24      | 4.524                    | 3.59           | 3.61           | 3.51           | 125     | 122.7                    | 97.3           | 97.9           | 95.1           |
| 25      | 4.909                    | 3.89           | 3.92           | 3.80           | 130     | 132.7                    | 105            | 106            | 103            |
| 26      | 5.309                    | 4.21           | 4.26           | 4.11           | 135     | 143.1                    | 113            | 114            | 111            |
| 28      | 6.158                    | 4.88           | 4.91           | 4.77           | 140     | 153.9                    | 122            | 123            | 119            |
| 30      | 7.069                    | 5.61           | 5.64           | 5.48           | 145     | 165.1                    | 131            | 132            | 128            |
| 32      | 8.042                    | 6.38           | 6.42           | 6.23           | 150     | 176.7                    | 140            | 141            | 137            |
| 34      | 9.079                    | 7.20           | 7.25           | 7.04           | 160     | 201.1                    | 159            | 160            | 156            |
| 35      | 9.616                    | 7.63           | 7.67           | 7.45           | 170     | 227.0                    | 180            | 181            | 176            |
| 36      | 10.18                    | 8.07           | 8.12           | 7.89           | 180     | 254.5                    | 202            | 203            | 197            |
| 38      | 11.34                    | 8.99           | 9.05           | 8.79           | 190     | 283.5                    | 225            | 226            | 220            |
| 40      | 12.57                    | 9.97           | 10.0           | 9.74           | 200     | 314.2                    | 249            | 251            | 243            |
| 42      | 13.85                    | 11.0           | 11.1           | 10.7           | 250     | 490.9                    | 389            | 392            | 380            |
| 44      | 15.21                    | 12.1           | 12.1           | 11.8           |         |                          |                |                |                |