

ステンレス四角棒SUS304 (ホット)

(切断売り)

JIS 規格名及記号 G4303 SUS304-B

配合 (%) Ni 8.0~10.50 Cr18.00~20.00

(単位: m/m)

C0.08 以下 Si1.00以下

Mn2.00以下 P0.045以下 S0.03以下

Fe残

仕 上 げ ホット (熱間圧延品)

比 重 7.93

外径寸法公差	28以下	±0.4
	30以上	±1.5 %

径 mm	長さ mm	1本重量 kg	無計量 採用	切断 可否	備考
10.0	4,000	3.17	○	可	
12.0	"	4.57	○	"	
13.0	"	5.36	○	"	
14.0	"	6.20	○	"	
15.0	"	7.12	○	"	
16.0	"	8.12	○	"	
19.0	"	11.40	○	"	
20.0	"	12.70	○	"	
22.0	"	15.40	○	"	
25.0	"	19.80	○	"	
26.0	"	21.44	○	"	
28.0	"	24.90	○	"	
30.0	"	28.60	○	"	
32.0	"	32.50	○	"	
36.0	"	41.20	○	"	
38.0	"	45.60	○	"	
40.0	"	50.80	○	"	
42.0	"	56.00	○	"	
45.0	"	64.40	○	"	
50.0	"	79.20	○	"	
55.0	"	96.00	○	"	
60.0	"	114.20	○	"	
65.0	"	134.00	○	"	
70.0	"	155.50	○	"	
75.0	"	178.00	○	"	
90.0	"	257.00	○	"	
100.0	"	318.00	○	"	

○印は無計量採用寸法です。

ステンレス四角棒（ホット）

（切断売り）

SUS316

径 mm	長さ mm	1本重量 kg	無計 探 量 用	切 断 可 否	表 面 仕 上	備 考
19	4,000	11.5	○	可	酸洗	
20	"	12.8	○	"	"	
22	"	15.4	○	"	"	
25	"	20.0	○	"	"	
30	"	28.7	○	"	"	
32	"	32.7	○	"	"	
38	"	46.0	○	"	"	
42	"	56.4	○	"	"	
50	"	80.0	○	"	"	

SUS316L

径 mm	長さ mm	1本重量 kg	無計 探 量 用	切 断 可 否	表 面 仕 上	備 考
19	4,000	11.5	○	可	酸洗	
20	"	12.8	○	"	"	
22	"	15.4	○	"	"	
25	"	20.0	○	"	"	
30	"	28.7	○	"	"	
32	"	32.7	○	"	"	
38	"	46.0	○	"	"	
42	"	56.4	○	"	"	
50	"	80.0	○	"	"	