

りん青銅丸棒

(切断売り)

(単位m/m)

JIS 規格名及記号 H3270 C5191B
 旧JIS 規格名及記号 H3741 PBB2 りん青銅棒 2種
 配合 (%) Sn 5.5~7.0 P 0.03~0.35
 Cu+Sn+P99.5 以上
 質 別 H
 比 重 8.89

外径公差	20以下		±0.08
	20を超え	35 "	±0.12
	35 "	40 "	±0.15
	40 "	50 "	±0.15
	50 "	150 "	±0.5%
	150以上		-0.+1.0

径 mm	長さ		1本重量 kg	無計量 採用	切断 可否	1m当り 参考重量kg	備 考
	mm	乱尺					
20.0	2,000		5.586	○	可	—	引拔
21.0	"		6.158	○	"	—	
22.0	"		6.759	○	"	—	
23.0	"		7.387	○	"	—	
24.0	"		8.044	○	"	—	
25.0	"		8.728	○	"	4.4	
26.0	"		9.440	○	"	4.7	
28.0	"		10.948	○	"	5.5	
30.0	"		12.568	○	"	6.3	
32.0	"		14.300	○	"	7.1	
34.0	"		16.143	○	"	8.1	
35.0	"		17.106	○	"	8.6	
38.0	"		20.165	○	"	10.1	
40.0	"		22.343	○	"	11.2	
42.0	"		24.633	○	"	12.3	
45.0	"		28.278	○	"	14.1	
46.0	"		19.549	○	"	14.8	
50.0	"		34.911	○	"	17.5	
55.0	"		42.242	○	"	21.2	
60.0	"		50.272	○	"	25.1	
65.0	"	*	59.000	×	"	29.5	鍛造
70.0	"	*	68.426	×	"	34.2	
75.0	"	*	78.550	×	"	39.3	
80.0	"	*	89.372	×	"	44.7	
85.0	"	*	100.893	×	"	50.4	
90.0	"	*	113.112	×	"	56.6	
95.0	"	*	126.029	×	"	63.0	
100.0	"	*	139.644	×	"	69.8	

○印は無計量採用寸法です。*印は長さ乱尺です。
 一口メモ 弊社のりん青銅丸棒は外径20ミリ以上が一般2種で、外径19ミリ迄が快削です。